

Technical Data Sheet (TDS)

Al-Siraj DELUXE Matt Emulsion Paint



DESCRIPTION	Al-Siraj Deluxe Matt Emulsion is high quality acrylic emulsion paint with very good adhesion, high hiding power, excellent washability and resistance to weathering properties
RECOMMENDED	used on all Interior and Exterior concrete, gypsum and wooden walls
TECHNICAL INFORMATION	
Colors	Catalogue
Solid Content by Weight %	55 ± 2%
Binder (Acrylate) by Weight %	20 %
Covering Rate	4-5 m ² /Lit. at 40 micron film
Drying Time at 30 °C	Touch dry : 15-20 min. Recoatable: 1 hrs. Full cure: 24 hrs
SURFACE PREPARATION	All surfaces to be painted must be clean, dry and sound free of faults, oils, grease, dust and contaminants
APPLICATION DATA	
Application Methods	Brush, Roller or Spray.
Mixing Ratio	10-20%
MISCELLANEOUS DATA	
Storage	Al-Siral Deluxe Matt Emulsion should be kept in cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
Shelf Life	48 months
Safety	<ul style="list-style-type: none">- Ensure good ventilation during application and drying.- Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner.- Keep out of reach of children.