

## Technical Data Sheet (TDS)

### Al-Siraj Vinyl Silk Emulsion Paint



<b>DESCRIPTION</b>	Al-Siraj Vinyl Silk gloss Emulsion is high quality acrylic emulsion paint with very good adhesion, high hiding power, excellent washability and resistance to weathering properties
<b>RECOMMENDED</b>	used on all Interior and Exterior concrete, gypsum and wooden walls
<b>TECHNICAL INFORMATION</b>	
<b>Colors</b>	Catalogue
<b>Solid Content by Weight %</b>	17 ± 1%
<b>Binder (Acrylate) by Weight %</b>	65 %
<b>Covering Rate</b>	4-5 m <sup>2</sup> /Lit. at 40 micron film
<b>Drying Time at 30 °C</b>	Touch dry : 15-20 min. Recoatable: 1 hrs. Full cure: 24 hrs
<b>SURFACE PREPARATION</b>	All surfaces to be painted must be clean, dry and sound free of faults, oils, grease, dust and contaminants
<b>APPLICATION DATA</b>	
<b>Application Methods</b>	Brush, Roller or Spray.
<b>Mixing Ratio</b>	10-20%
<b>MISCELLANEOUS DATA</b>	
<b>Storage</b>	Al-Siral vinyl silk Emulsion should be kept in cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
<b>Shelf Life</b>	48 months
<b>Safety</b>	<ul style="list-style-type: none"><li>- Ensure good ventilation during application and drying.</li><li>- Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner.</li><li>- Keep out of reach of children.</li></ul>