

## Technical Data Sheet (TDS)

### Enamel Siraj Paint



<b>DESCRIPTION</b>	Enamel Siraj Paint It is an alkyd based, serial dried and high thickness paint due to its good adhesion to metal surfaces and filling the pores on the surface.
<b>RECOMMENDED</b>	All areas requiring rapid drying; for the protection of metal surfaces in industrial facilities, ports, bridges etc. in the marine atmosphere, storage facilities
<b>TECHNICAL INFORMATION</b>	
<b>Colors</b>	Al-Siraj Catalogue
<b>Solid Content by Weight %</b>	30 ± 1%
<b>Binder (Alkyde) by Weight %</b>	40 %
<b>Covering Rate</b>	3-4 m <sup>2</sup> /Lit. at 40 micron film
<b>Drying Time at 25 °C</b>	Surface Drying: 10-30 minutes Full Drying: 5-6 hour Hard Drying: 72 hours
<b>SURFACE PREPARATION</b>	If the application is to be made directly to the metal surface, all kinds of oil dirt and rust on the surface (sanded, scraped, burned or washed with solvent) should be cleaned
<b>APPLICATION DATA</b>	
<b>Application Methods</b>	Brush, Roller or Spray
<b>Dilution</b>	The dilute by solvents such thinner, toluene and Kerosin, etc
<b>MISCELLANEOUS DATA</b>	
<b>Storage</b>	Should be kept in cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
<b>Shelf Life</b>	48 months
<b>Safety</b>	- Ensure good ventilation during application and drying. - Keep out of reach of children. <b>Notes: all product of Siraj enamel paint are lead-free.</b>

**Web:** [Sirajpaint-factory.com](http://Sirajpaint-factory.com)  
**E-mail:** [sirajfactory5@gmail.com](mailto:sirajfactory5@gmail.com)  
**Phone No:** (+964) 7701684980 , (+964) 7510513643  
**Adress:** Iraq- Nineveh- Telkeef- Almanar vil.